



广州丰江电池新技术股份有限公司
GUANGZHOU FENGJIANG NEW BATTERY TECHNOLOGY CO., LTD
Tel: 020-84821680 Fax: 020-84826301 <http://www.fentbattery.com>

Material Safety Data Sheet

1. Product & Company Identification:

Product	Li-Ion Polymer Rechargeable Battery		
Manufacturer:	Guangzhou Fullriver New Battery Technology Co., Ltd.		
Models:	503236		
Chemical system:	Graphite/Lithium Cobalt Oxide		
Nominal Capacity:	320mAh		
Nominal Voltage:	Single: 3.7V		
Address:	No.3,Dongli Road,Xili, Dongyong Town, Nansha District, Guangzhou City,China		
Telephone:	86-20-84821680	Fax:	86-20-84826301

2. Composition /Information on Ingredients:

Important note: The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

MATERIAL OR INGREDIENT	PEL (OSHA)	TLV (ACGIH)	%/wt.
Graphite (CAS# 7782-42-5)	5mg/m ³ TWA (respirable fraction) 15mg/m ³ TWA(total dust)	2mg/m ³ TWA (respirable fraction)	15~35
Lithium Cobalt Oxide (CAS# 12190-79-3)	0.1 mg/m ³ TWA (as Co)	0.02mg/m ³ TWA (as Co)	20~50
Lithium Hexafluorophosphate (CAS# 21324-40-3)	None established	None established	0~5
Acetylene Black (CAS# 1333-86-4)	3.5mg/m ³ TWA (as carbon black)	3.5mg/m ³ TWA(as carbon black)	0~10
Diethyl Carbonate (CAS# 105-58-8)	None established	None established	0-30



广州丰江电池新技术股份有限公司
GUANGZHOU FENGJIANG NEW BATTERY TECHNOLOGY CO., LTD
Tel: 020-84821680 Fax: 020-84826301 <http://www.fentbattery.com>

Material Safety Data Sheet

Dimethyl Carbonate (CAS# 616-38-6)	None established	None established	0~30
Ethyl Methyl Carbonate (CAS# 623-53-0)	None established	None established	0~30
Propylene Carbonate (CAS# 108-32-7)	None established	None established	0~30
Ethylene Carbonate (CAS# 96-49-1)	None established	None established	0~30



Material Safety Data Sheet

3. Hazardous Identification:

Chemical Nature: White color solid

CAS-No/EINECS NO.:N/A

INCI CTFA-Description:Lithium ion polymer rechargeable battery series

Ingestion: No effect under routine handling and use.

Inhalation: No effect under routine handling and use.

Skin contact: No effect under routine handling and use.

Eye contact: No effect under routine handling and use.

Skin absorption: No effect under routine handling and use.

Reported as carcinogen: Not applicable

4. First Aid Measures:

Under normal conditions of use, the battery is hermetically sealed.

Ingestion:

Swallowing a battery can be harmful.

Contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract. If battery or open battery is ingested, do not induce vomiting or give food or drink. Seek medical attention immediately.

Inhalation:

Contents of an open battery can cause respiratory irritation. Inhalation of vapors may cause irritation of the upper respiratory tract and lungs. Provide fresh air and seek medical attention.

Skin Absorption:

Ethylene carbonate, diethyl carbonate and dimethyl carbonate may be absorbed through the skin causing localized inflammation.

Skin Contact:

Contents of an open battery can cause skin irritation and/or chemical burns. Remove contaminated clothing and wash skin with soap and water. If a chemical burn occurs or if irritation persists, seek medical attention.



Material Safety Data Sheet

Eye Contact:

Contents of an open battery can cause severe irritation and chemical burns. Immediately flush eyes thoroughly with water for at least 15 minutes, lifting upper and lower lids, until no evidence of the chemical remains. Seek medical attention.

Note:

Acetylene black and cobalt compounds are listed as possible carcinogens by the International Agency for Research on Cancer (IARC).

5. Fire Fighting Measures

If fire or explosion occurs when batteries are on charge, shut off power to charger.

In case of fire where lithium ion batteries are present, flood the area with water. If any batteries are burning, water may not extinguish them, but will cool the adjacent batteries and control the spread of fire. CO₂, dry chemical, and foam extinguishers are preferred for small fires, but also may not extinguish burning lithium ion batteries. Burning batteries will burn themselves out. Virtually all fires involving lithium ion batteries can be controlled with water. When water is used, however, hydrogen gas may be evolved which can form an explosive mixture with air. LITH-X (powdered graphite) or copper powder fire extinguishers, sand, dry ground dolomite or soda ash may also be used. These materials act as smothering agents.

Fire fighters should wear self-contained breathing apparatus. Burning lithium ion batteries can produce toxic fumes including HF, oxides of carbon, aluminum, lithium, copper, and cobalt. Volatile phosphorus pent fluoride may form at a temperature above 230° Fahrenheit.

6. Accidental Release Measures

On hand: Place material into suitable containers and call local fire/police department.



Material Safety Data Sheet

In water: If possible. Remove from water and call local fire/police department.

7. Handling & Storage

Handling: Do not expose the battery to excessive physical shock or vibration. Short-circuiting should be avoided; however, accidental short-circuiting for a few seconds will not seriously affect the battery. Prolonged short circuits will cause the battery to rapidly lose energy, could generate enough heat to burn skin. Sources of short circuits include jumbled batteries in bulk containers, coins, metal jewelry, metal covered tables, or metal belts used for assembly of batteries in devices. To minimize risk of short-circuiting, the protective case supplied with the battery should be used to cover the terminals when transporting or storing the battery. Do not disassemble or deform the battery. Should an individual cell within a battery become ruptured, do not allow contact with water.

Storage: The lithium ion battery should be between 25% and 75% of full charge when stored for a long period of time. Stored in a cool, dry, and well ventilated area. Elevated temperatures can result in loss of battery performance, leakage, or rust. Do not expose the battery to open flames.

8. Exposure Control/Personal Protection

Engineering Control:

Keep away from heat and open flame. Stored in a cool dry place.

Personal Protection:

Respiratory Protection: Not necessary under normal conditions.

Eye/Face Protection:

Not necessary under normal conditions. Wear safety glasses with side shields if handling an open or leaking battery.

Gloves:

Not necessary under normal conditions. Use neoprene or natural rubber



Material Safety Data Sheet

gloves if handling an open or leaking battery.

Foot Protection:

Steel toed shoes recommended for large container handling.

9. Physical/Chemical Properties

Physical state	Solid	Solubility in water:	Not Applicable
Color	White	Vapor pressure	Not Applicable
Odor	No	Explosion limit	Not Applicable
Flash point	Not Applicable	Auto flammability	Not Applicable
Solubility in ethanol soluble	Not Applicable	Melting Point	Not Applicable
Boiling Point	Not Applicable	Freezing Point	Not Applicable
Energy	0.01~60Wh (Note:Wh=nominal voltage × Rated Ah, marked on each battery)		

10. Stability & Reactivity

Stability: Good stability at standard temperature.

Reactivity: None

Avoid contact with water and acids. Hazardous decomposition products: If Al package foil of battery is damaged, the battery should avoid to contact strong oxidizer, acids and high temperature, and the electrolyte will be formed HF.

11. Toxicological information

This product does not elicit toxicological properties during routine handling and use.

12. Ecological information

If the battery is scrapped, it should be selected and disposed by professional company.

13. Disposal considerations

Do not dispose of battery into environment or sewerage. It should be



Material Safety Data Sheet

recycled and disposed basing on your local legislation and regulations.

14. Transport Information

The watt-hour rating of the battery models listed is not more than 100Wh. The product is not classified as dangerous under the current edition (According to PACKING INSTRUCTION 965-967 Section II of IATA DGR 59th Edition for transportation, or the special provision 188 of IMDG) of the IATA dangerous goods regulations. The product is safe for air/sea transportation and not regulated by IATA DGR.

Each package is labelled and well passed the 1.2m drop test. The manufacture data is labelled on each battery.

No	ITEMS	RESULT	REMARKS
1	Altitude simulation	Pass	Test 1 to 5 must be conducted in sequence on the same cell or battery
2	Thermal test	Pass	
3	Vibration	Pass	
4	Shock	Pass	
5	External short circuit	Pass	
6	Impact	Pass	
7	Overcharge	Pass	Only battery do need this test
8	Forced Discharge	Pass	

15. Regulatory Information

See ACGIH exposure limits information as noted in Section3.

US: This MSDS meets/exceeds OSHA requirements.

International: This MSDS conforms to European Union (UN), the International Standards Organization (ISO) and the International Labor Organization (ILO) and as documental in ANSI (American National Standards Institute) Standard Z400.1-1993.



广州丰江电池新技术股份有限公司
GUANGZHOU FENGJIANG NEW BATTERY TECHNOLOGY CO., LTD
Tel: 020-84821680 Fax: 020-84826301 <http://www.fentbattery.com>

Material Safety Data Sheet

16. other information

Prepared Department: Tech Dept. GUANGZHOU FULLRIVER BATTERY NEW TECHNOLOGY CO.,LTD

Reviewed Department: Quality Dept. GUANGZHOU FULLRIVER BATTERY NEW TECHNOLOGY CO.,LTD

PS.1. UN Manual of Test and Criteria, Part 111, Sub-section 37.3 is met.

PS.2. The latest IATA requirement is met.